



TDS技术数据表 Technical Data Sheet

NX-5105 热熔胶 Hot Melt Adhesive

产品编号 Product Number	NX-5105	制表人 Data Sheet maker	涂苏青 Tu Suqing	制表日期 Date	2026年1月
------------------------	---------	-------------------------	------------------	--------------	---------

一、产品用途与特性 Product Usage and Characteristics


较高的初期粘力, 较低的熔融粘度, 良好的低温性能, 拉丝少。

Good initial adhesive, low melt viscosity, good low temperature resistance, less drawing.

二、产品技术指标 Product Technical Indicators

产品型号 Production Number	NX-5105
外观 Appearance	白色透明状固体 White translucent solid
软化点 Softening point	加热至 $90\pm 5^{\circ}\text{C}$ Heat up to $90\pm 5^{\circ}\text{C}$
熔胶粘度 Opening Time	2000 cps/ 160°C
使用温度 Application Temperature	$130-150^{\circ}\text{C}$, 由基材、设备和操作方法决定。 $130-150^{\circ}\text{C}$, decided by the base materials, equipment and operation method.
储存期 ($5-35^{\circ}\text{C}$) Storage period	2年 2 years

三、使用流程 Application Process



四、注意事项 Attention:

1. 准确辨别材质, 选用适用的产品。

Accurately identify the material and choose the appropriate products.

2. 大量使用前先试胶确认。

Please do the adhesive trial SOP confirmation before mass production.

3. 此产品溶解于胶槽温度极高, 请勿触摸, 以免烫伤。

This product is dissolved in the glue tank at a very high temperature, do not touch it to avoid burns.

4. 此产品纯环保对环境、健康无危害, 但不可食用。

This product is pure environmental protection, no harm to the environment and health, but not edible.